



FAN JET

Fan jets are water level independent and water supply must be linear, non turbulent.

EFFICIENCY ●●●○○
 VISIBILITY ●●●●● SOUND LEVEL ●●●○○
 WIND RESISTANCE ●●●○○ SPLASH / MIST ●●●○○



ML 100

ML 150

Material		Stainless Steel AISI 304 or 316 on Request				Stainless Steel AISI 304 or 316 on Request				
Inlet BSP/NPT	1"					1½"				
Nozzle s Orifice (C)	4 mm					6 mm				
Dimensions A X B in mm	120 x 83					166 x 113				
45° Elbow	Included					Included				
Suction Strainer Openings Required	3.0 mm					8.0 mm				
Spray Length (J)	Height (H)	Spread (F)	Spread at Max. Height (G)	Flow	Head	Height (H)	Spread (F)	Spread at Max. Height (G)	Flow	Head
0.5 m	0.18 m	0.25 m	0.20 m	40.6 Lpm	0.4 m	0.20 m	0.24 m	0.17 m	71.3 Lpm	0.5 m
1.0 m	0.32 m	0.50 m	0.34 m	64.3 Lpm	1.0 m	0.35 m	0.44 m	0.33 m	106.5 Lpm	0.8 m
1.5 m	0.46 m	0.80 m	0.52 m	83.6 Lpm	1.6 m	0.45 m	0.70 m	0.50 m	137.4 Lpm	1.2 m
2.0 m	0.59 m	1.10 m	0.70 m	90.0 Lpm	2.2 m	0.60 m	0.95 m	0.70 m	162.3 Lpm	1.6 m
2.5 m	0.70 m	1.43 m	0.87 m	109.8 Lpm	2.8 m	0.70 m	1.05 m	0.80 m	186.3 Lpm	2.0 m
3.0 m	0.85 m	1.80 m	0.98 m	123.3 Lpm	3.4 m	0.87 m	1.35 m	1.00 m	207.1 Lpm	2.5 m
3.5 m						1.00 m	1.68 m	1.10 m	229.6 Lpm	2.9 m
4.0 m						1.18 m	1.78 m	1.20 m	123.3 Lpm	3.3 m





FAN JET

