

## **SMOOTH**

## **Technical features**

## SMOOTH JET PLUS now ship with an internal flow straightener\*

This is a great little accessory which does some remarkable work. It eliminates pumps turbulence and straightens the incoming water. The stream then comes out higher, smoother and crystal-clear. The flow straightener is firmly placed inside the nozzle without affecting its dimensions.



	L3 1013	L310E0
	Stainless Steel AISI 304 or 3016 on Request	
Inlet BSP/NPT	11/2"	1½"
Nozzle Orifice ( D )	17 mm	20 mm
<b>Dimensions</b> AxB in mm	54 x 153	54 x 153
<b>Integrated</b> Swivel Ball Joint	±15°	±15°
Spray Height ▼	FLOW   Head (LPM)   [m]	FLOW   Head (LPM)   [m]
0.5 m	43   1.0	0.7 59
1.0 m	61   1.4	1.1   82
1.5 m	76   1.9	1.9   104
2.0 m	87   2.4	2.4   119
2.5 m	98   2.9	3.1   135
3.0	108   3.3	3.6   147
3.5	118   4.2	4.2   159
4.0	124   4.6	4.8   170
5.0	133   5.2	6.1   191
6.0	5.8   143	7.3   211
7.0	7.0   156	8.6   235
8.0	8.2   169	9.8   259
9.0	9.3   181	11.0   273
10.0	10.6   192	12.2   290









